


Universal Tooling Receiver

Features & Benefits

- Utilizes anti-rotational (square design) tooling receivers and adapters which also provides generous clearance for quick tooling changeover.
- Incorporates the FLEX Cam Lock, which is a rugged cam operated lever used as the primary lock for the tooling adapter.
- Includes an automatic detent latch which provides double the protection for securing the tooling adaptor in place.
- Provides automatic connection of electrical for part detection and pneumatic for clamping (if required).
- Receiver/Adaptor interface offers mechanical coding which insures proper tool placement in the correct receiver.
- Incorporates light weight components to improve transfer performance.
- Easier changeover, handling and storage of fingers.
- Hard coated aluminum reduces wear & nicking.
- Compact design makes mounting easy.
- More economical than permanently mounted dedicated rail systems.
- Compatible with 1" & 1-1/4" diameter tooling fingers.

Component Selection & Sizes


- Basic with no option: #S.125.AA.060
- With pneumatic option: #S.125.AA.061
- With electric option-3 Pin: #S.125.AA.066
- With electric option-4 Pin: #S.125.AA.067
- With Mechanical option: #S.125.AA.070
- With electric and pneumatic option:
 - 3 Pin: #S.125.AA.072
 - 4 Pin: #S.125.AA.073
- With electric, pneumatic, & mechanical option:
 - 3 Pin: #S.125.AA.076
 - 4 Pin: #S.125.AA.077



U.S. Patent No. 6,427,996

If you are purchasing our Universal Tooling Receiver, you might also want to look at:

- *Universal Tooling Adapter*
- *Tooling Arms*
- *Universal Tooling Rails*



Additional components can also be found online in our Tooling section at www.atlastechnologies.com.